


SOT-89 PNP Silicon PNP transistor in a SOT-89 Plastic Package.

, 2SD1766

Low $V_{CE(sat)}$, complements the 2SD1766.

Medium power amplifier applications.




PIN1 Base PIN 2 Collector PIN 3 Emitter

h_{FE} Classifications Symbol	P	Q	R
h_{FE} Range	82 180	120 270	180 390
Marking	HBCP	HBCQ	HBCR


Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	-40	V


Colle



SIT-89

单位: mm





H

BC

P h_{FE}

**

Note:


H: Company Code.

BC: Product Type.

P h_{FE} Classifications Symbol

** : Lot No. Code, code change with Lot No.

K\ d g\ i Xk\ i \ 'Gif] \ d] fi @ ' l \] f n J f d \ i e ^ Z G Y \$ = i \ \ z



Note:

- | | | | | | |
|---|-------|-----|-----------|--------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | | 5±0.5sec; | | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | | 2 | 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

260±5

10±1 sec.

Temp.:260±5

Time:10±1 sec

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-89	1,000	7	7,000	8	56,000	7 ×12	180×120×180	385×257×392