

/ Descriptions

SOT-89 NPN Silicon NPN transistor in a SOT-89 Plastic Package.


/ Features

h_{FE} , V_{CEO} , 2SA812T
High h_{FE} and V_{CEO} , complementary pair with 2SA812T.


/ Applications

Audio frequency general amplifier application.

/ Equivalent Circuit



/ Pinning




PIN1 Base PIN 2 Collector PIN 3 Emitter

/ Marking

h_{FE} Classifications Symbol	O	Y	G	L
h_{FE} Range	90 180	135 270	200 400	300 600
Marking	HL4	HL5	HL6	HL7

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	60	V
Collector to Emitter Voltage	V_{CEO}	50	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current-Continuous	I_C	100	mA
w()Tj10.5 0	0	10.5	330.12


/ Electrical Characteristic Curve



/ Package Dimensions


SOT-89

单位: mm



Symbol	Dimensions in millimeters		Symbol	Dimensions in millimeters	
	Min	Max		Min	Max
A	4.4	4.7	a1	0.36	0.56
a	2.35	2.55	a2	0.30	0.50
B	3.878	4.478	C	1.40	1.70

/ Marking Instructions



H

L5

**


Note:

H: Company Code.

L5: Product Type.

** : Lot No. Code, code change with Lot No.

() / K\d g\iXk i\`Gif]`d`]fi`@`l`]\`fn`Jfd` \i`e`^ZGY\$`i`\\z



Note:

- | | | | | | |
|---|-------|-----|----|-----------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | | | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | | | 2 | 10 /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-89	1,000	7	7,000	8	56,000	7 ×12	180×120×180	385×257×392

/ Notices