

/ Descriptions

SOT-89 NPN Silicon NPN transistor in a SOT-89 Plastic Package.



/ Features

h_{FE} , 1W , 2SA1204
High h_{FE} , for out stage of 1 watts amplifier, complementary to 2SA1204.

/ Applications

Audio frequency amplifier applications

/ Equivalent Circuit




PIN1 Base PIN 2 Collector PIN 3 Emitter

/ Marking


h_{FE} Classifications Symbol	O	Y
h_{FE} Range	100 200	160 320
Marking	HPO * *	HPY

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	V_{CBO}	35	V
Collector to Emitter Voltage	V_{CEO}	30	V
Emitter to Base Voltage	V_{EBO}	5.0	V
Collector Current-Continuous	I_C	800	mA

/ Electrical Characteristic Curve



/ Marking Instructions



H

P

O

h_{FE}

**

Note:


H: Company Code.

P: Product Type.

O h_{FE} Classifications Symbol

** : Lot No. Code, code change with Lot No.

() / K\d g\iXk\i\`Gif]`d`]fi`@`I\`]fn`Jfd\`i`e`^ZGY\$`i\`z



Note:

- | | | | | | |
|---|-------|-----|----|-----------|---|
| 1 | 25 | 150 | 60 | 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | | | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | | | 2 | 10 /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Reel 只/卷盘	Reels/Inner Box 卷盘/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Reel	Inner Box 盒	Outer Box 箱
SOT-89	1,000	7	7,000	8	56,000	7 ×12	180×120×180	385×257×392