

**/ Descriptions**

KF \$0) E GE Silicon NPN transistor in a TO-92 Plastic Package.


**/ Features**

# # # )JB(' - /  
low saturation voltage, high DC current gain, high total power dissipation  $P_C$  Complementary pair with 2SB1068.

**/ Applications**

For use in driver and output stages of audio frequency amplifiers.

**/ Equivalent Circuit**



**/ Pinning**






PIN1 Base PIN 2 Collector PIN 3 Emitter

**/ hFE Classifications & Marking**

h <sub>FE</sub> Classifications Symbol	L	K	U
h <sub>FE</sub> Range	135~270	200~400	300~650

Parameter	Symbol	Rating	Unit
Collector to Base Voltage	$V_{CBO}$	20	V
Collector to Emitter Voltage	$V_{CEO}$	16	V
Emitter to Base Voltage	$V_{EBO}$	6.0	V
Collector Current - Continuous	$I_C$	2.0	A
Collector Current – Continuous(Pulse)	$I_{CP}$	3.0	A
Collector Power Dissipation	$P_C(T_a=25 \text{ } ^\circ\text{C})$	750	mW


/ Electrical Characteristic Curve




/ Package Dimensions

TO-92

Unit: mm



/ Marking Instructions



BI 1

; (, (\*

L1                     $h_{FE}$

\*\*\*\*

Note:


BR:                    Company Code.

D1513:                Product Type.

L:                       $h_{FE}$  Classifications Symbol

\*\*\*\*:                   Lot No. Code,code change with Lot No.

( ) / Temperature Profile for Dip Soldering(Pb-Free)



Note:

- |   |       |     |           |        |   |
|---|-------|-----|-----------|--------|---|
| 1 | 25    | 150 | 60        | 90sec; | 1.Preheating:25~150 , Time:60~90sec.    |
| 2 | 255±5 |     | 5±0.5sec; |        | 2.Peak Temp.:255±5 , Duration:5±0.5sec. |
| 3 |       | 2   | 10        | /sec.  | 3. Cooling Speed: 2~10 /sec.            |

/ Resistance to Soldering Heat Test Conditions

270±5                      10±1 sec.                      Temp:270±5                      Time:10±1 sec

/ Packaging SPEC.

/ BULK

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm3)		
	Units/Bag 只/袋	Bags/Inner Box 袋/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Bag 袋	Inner Box 盒	Outer Box 箱
TO-92	1,000	10	10,000	5	50,000	135×190	237×172×102	560×245×195
	1,000	10	10,000	10	100,000	135×190	237×172×102	560×245×375

/ AMMO

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm3)	
	Units/tape 只/纸带	Tape/Inner Box 纸带/盒	Rows/Inner Box 纸带层/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Inner Box 盒	Outer Box 箱
TO-92	3,000	1	120	10	30,000	328×230×42	小箱 480×346×235, 大箱 547×407×268

/ Notices