



%	&' ( ) * ( ( * +		, - +) . ' / 0 1 2	3 4 5	
%	& & * 6 *		$\Delta V_{Load}$ $\Delta V_{Line}$ 8) ' 76' 79' 7: ' ; < ( ' ' 7/ ' 7( ' ' 7/ ' = > ? / " @ 0 1 2 A B < ~ C 0 1 2 D	E F	3 4 5

**78B05A**  
Rev.A Apr.-2020





**DATA SHEET**


TO-263 G H H I J K L MN




/ Electrical Characteristic Curve



**78B05A**  
Rev.A Apr.-2020



( ) / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- |   |       |     |    |           |   |
|---|-------|-----|----|-----------|---|
| 1 | 150   | 180 | 60 | 90sec;    | 1.Preheating:150~180 , Time:60~90sec.   |
| 2 | 245±5 |     |    | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 |       |     | 2  | 10 /sec.  | 3. Cooling Speed: 2~10 /sec.            |

/ Resistance to Soldering Heat Test Conditions

260±5                      10±1 sec.                      Temp:260±5°C                      Time:10±1 sec

/ Packaging SPEC.

/                      E

