

9 5 : .> // x 9 ² ... ~ož Voltage Regulator in a SOT-89 Plastic Package.

€19²... ~k ÿ ß v ä S' Ä — ½ ' y ? è ' ò k —)í D }ož
3-Terminal regulators ,output current up to 100 mA, internal thermal overload protection and short-circuit limiting, HF Product.

9 ² ... ~ož
Voltage Regulator.

*

$@ f$ Parameter	$\dots Z$ Symbol	$f \succ$ Rating	$\% y$ Unit
Input voltage	V_I	30	V
Output current	I_o	100	mA
Operating Temperature Range	T_{OPR}	-40 125	
Power Dissipation	P_D	500	mW
Storage temperature range	T_{stg}	-55 150	
Thermal resistance junction-ambient	R		

Ô ? d • Ž ç w [(D)-

Ø □ =) ϕ / Package Dimensions

, M y f / Marking Instructions

HL05 **

^a ç y

H y , [W A

L05 y ° Z W A

y ÿ D Z W A k š ÿ D Z J

Note:


H: Company Code

L05: Product Type Code

** : Lot No. Code, code change with Lot No.

šWD t... •Žç (x/) / :KSVKXGZ[XK 6XULORK LUX /8 8KLRU] 9URJKXOTM 6

7HPSHUDWXUH



7LPH VHF

^açy

1o• Ä ½ “ † 150 ½180 - k ž • 60 ½90sec;

2o• Q › “ † 245 r5 - k ž • 4 Ò 5 r0.5sec;

3o•D N ò i Ò 0 , † 2 ½10 - /sec.

Note:

1.Preheating:150~180 - , Time:60~90sec.

2.Peak Temp.:245 r5 - , Duration:5 r0.5sec.

3. Cooling Speed: 2~10 - /sec.

ÂD /Cã p ~ »] / Resistance to Soldering Heat Test Conditions

“ † y 260 r5 -

ž • y 10 r1 sec.

Temp.:260±5

Time:10±1 sec

G P á / Packaging SPEC.

2 & x / REEL

Package Type 7>û ~ E	Units ;>û :H					Dimension ;>û p . (unit Åmm³)		
	Units/Reel /--	Reels/Inner Box -- /-	Units/Inner Box /-	Inner Boxes/Outer Box - /1ç	Units/Outer Box /1ç	Reel	Inner Box	Outer Boxç
SOT-89	1,000	7	7,000	6	42,000	7 s x12	180x120x180	390x385x205

„Đ y f / Notices