

5 é

TO-220 ~~Ⓢ~~
Voltage Regulator in a TO-220 Plastic Package.

~~Ⓢ~~ ~~Ⓢ~~
~~Ⓢ~~



AEC-Q100 ~~Ⓢ~~

3-Terminal regulators ,output current up to 1.5A, internal thermal overload protection and short-circuit limiting, Qualified to AEC-Q100 Standards for High Reliability, HF Product.

~~Ⓢ~~ ~~Ⓢ~~

Voltage Regulator, Meet the stringent requirements of automotive applications.

~~Ⓢ~~ ~~Ⓢ~~ ~~Ⓢ~~ / ~~Ⓢ~~ ~~Ⓢ~~ ~~Ⓢ~~ / **Equivalent Circuit or Application Circuit**



PIN1y GND

PIN 2y IN



PIN 3y OUT

, M V / **Marking**

~~Ⓢ~~

See Marking Instructions.


∅ ≡) ∅ / Package Dimensions



Dim	Min	Max	Symbol	Min	Max	Symbol
q_1	1.2	1.4	A	9.8	10.2	C
B	6.3	6.7	R	3.56	3.64	
q_2	9.0	9.4		15.7	16.1	
C_1	2.2	2.6	h	12.6	13.6	



, M y f / Marking Instructions



Q
(S) W
Qy D
y D
y W

Note:
BR: Company Code
Q: Automobile halogen-free product Code
7915: Product Type
****: Lot No. Code, code change with Lot No

BR7915Q
Rev.A Jul.-2024