

Rev.A Apr.-2023


SOT-323

Silicon Diode in a SOT-323 Plastic Package.

AEC-Q101

Small signal diode, Qualified to AEC-Q101 Standards for High Reliability, HF Product.

High Conductance Ultra Fast Diode, Meet the stringent requirements of automotive applications.



PIN: See Equivalent Circuit.


Marking	QA4
---------	-----

Rev.A Apr.-2023

Parameter	Symbol	Rating	Unit
Maximum Repetitive Reverse Voltage	V_{RRM}	75	V
Breakdown Voltage	V_R	70	V
Average Rectified Forward Current	$I_{F(AV)}$	200	mA
Non-repetitive Peak Forward Surge Current	$I_{FSM(1)}(\text{pulse width}=1.0S)$	1.0	A
	$I_{FSM(2)}(\text{pulse width}=1.0mS)$	2.0	A
Power Dissipation	P_D	350	mW

24407.275.36.46 571.04 .47.5 64.32 557.4803 Tm.4810.365w()Tj/Tw[verag)-5.pul)8.3()-5.3(ent4(d15)5A)2.6(V)5f9.9-8780 0 7.0

Rev.A Apr.-2023



Q

A4

Note:

Q: Automobile halogen-free product Code

A4: Product Type Code

