

BRCS012N03SZC

Rev.B Oct.-2025

/ Descriptions

PDFN 5×6 N

N-Channel MOSFET in a PDFN5×6 Plastic Package .

/ Features

$V_{DS}(V)=30\text{ V}$ $I_D=212\text{ A}$

$R_{DS(ON)}@10\text{ V}$ 1.3m (Typ.1.2m)

$R_{DS(ON)}@4.5\text{ V}$ 2.5m (Typ.1.8m)


HF Product.

/ Applications


LED

This device is ideal for boost converters and synchronous rectifiers for consumer,telecom, industrial power supplies and LED backlighting.

/ Equivalent Circuit



/ Pinning



PIN1 2 3 S PIN4 G PIN5 6 7 8 D

/ Marking

See Marking Instructions.

/ Absolute Maximum Ratings($T_c=25$)

Parameter		Symbol	Rating	Unit
Drain-Source Voltage		V_{DS}	30	V
Drain Current		I_D	212	A
Drain Current - Pulsed		I_{DM}	345	A
Gate-Source Voltage		V_{GS}	± 20	V
Single Pulsed Avalanche Energy		E_{AS}	703	mJ
Avalanche Current		I_{AS}	37.5	A
Power Dissipation		P_D	100	W
Operating and Storage Temperature Range		T_J, T_{stg}	-55 to 150	
Junction-to-Ambient	$t = 10$	R_{JA}	20	/W
Junction-to-Ambient	Steady-State		60	
Junction-to-Case	Steady-State	R_{JC}	1.25	

/ Electrical Characteristics($T_c=25$)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V$ $I_D=250\mu A$	30			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=30V$ $V_{GS}=0V$			1	μA
Gate-Body Leakage Current Forward	I_{GSS}	$V_{GS}=\pm 20V$ $V_{DS}=0V$			± 0.1	μA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=250\mu A$	1.1		2.2	V
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V$ $I_D=30A$		1.2	1.3	m
		$V_{GS}=4.5V$ $I_D=20A$		1.8	2.5	m
Drain-Source Diode Forward Voltage	V_{SD}	$V_{GS}=0V$ $I_S=1A$			1.2	V
Reverse Recovery Time	t_{rr}	$V_{DS}=15V, I_D=20A$ $dI_{SD}/dt = 100 A/\mu s$		38.2		ns
Reverse Recovery Charge	Q_{rr}			37.7		nC
Input Capacitance	C_{iss}	$V_{DS}=25V$ $V_{GS}=0V$ $f=1.0MHz$		3040		pF
Output Capacitance	C_{oss}			1110		
Reverse Transfer Capacitance	C_{rss}			40		
Gate resistance	R_g	$V_{GS}=0V$ $V_{DS}=0V$ $f=1MHz$		3.3		

BRCs012N03SZC




Rev.B Oct.-2025






DATA SHEET

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Total Gate Charge	$Q_{g(10V)}$	$V_{GS}=10V$ $V_{DS}=15V$ $I_D=20A$		43.5		nC
Total Gate Charge	$Q_{g(4.5V)}$			19.4		
Gate Source Charge	Q_{gs}			5.5		
Gate Drain Charge	Q_{gd}			8.1		

/ Electrical Characteristic Curve




/ Electrical Characteristic Curve



/ Package Dimensions

PDFN5 X6

Unit:mm



Rev.02 202510

/ Marking Instructions



BR

012N03S

Note

BR

Company Code

012N03S

Product Type

****:

Lot No. Code, code change with Lot No.



() /

Note:

- | | | | |
|---|---------|-----------|---|
| 1 | 150 180 | 60 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245±5 | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | 2 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5	10±1 sec.	Temp.:260±5	Time:10±1 sec
-------	-----------	-------------	---------------

w b ç 0 R @ ìx

/ Packaging SPEC.

k ž REE F / " IO 5 Q ā P Q ' = D p u q ñ " ì t 6) q P Đ