

BRCS035N06SZC

Rev.C Feb.-2023

/ Descriptions

PDFN5×6 N

N-Channel MOSFET in a PDFN5x6 Plastic Package .


/ Features

Low $R_{DS(ON)}$ to minimize conductive loss;low Gate Charge for fast switching;Low Thermal resistance;HF Product.


/ Applications

MB/NB/UMPC/VGA Buck -
Battery Management,High Frequency Point-of-Load Synchronous Buck Converter for MB/NB/UMPC/VGA,Networking DC-DC Power System,Load Switch.

/ Equivalent Circuit



/ Pinning



PIN1 2 3 S PIN4 G PIN5 6 7 8 D

Pin	极性
1	S
2	S
3	S
4	G
5	D
6	D
7	D
8	D

/ Marking

See Marking Instructions.

BRCs035N06SZC

Rev.C Feb.-2023




Parameter	Symbol	Rating	Unit
Drain-Source Voltage	V_{DS}	60	V
Continuous Drain Current	I_D	111	A
Pulsed Drain Current	I_{DM}	227	A
Gate-Source Voltage	V_{GS}	± 20	V
Power Dissipation	$P_D(T_c=25^\circ\text{C})$	78	W
Avalanche energy(L=0.5mH)	E_{AS}	2000	mJ
Avalanche Current(L=0.5mH)	I_{AS}	47	A

Junction and Storage Temperature $T_{J,ST}$

/ Electrical Characteristics(Ta=25)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=10V$ $V_{DS}=30V$ $R_L=1.5$ $R_{GEN}=3$		13		ns
Turn-On Rise Time	t_r			4		
Turn-Off Delay Time	$t_{d(off)}$			47		
Turn-Off Fall Time	t_f			6.5		

/ Electrical Characteristic Curve



/ Electrical Characteristic Curve





Figure 10: Maximum Forward Bias Safe Operating Area vs Case Temperature

Figure 9: Maximum Forward Bias Safe Operating Area




Figure 11: Maximum Thermal Impedance vs Pulse Width

/ Package Dimensions

PDFN5 X6

Unit:mm PDFN5 X6

Dimensions In Millimeter			Symbol
MIN	TYP	MAX	

/ Marking Instructions

BR

035N06S

Note

BR Company Code

035N06S Product Type Code

****: Lot No. Code, code change with Lot No



() / Temperature Profile for IR Reflow Soldering(Pb-Free)

Note:

- | | | | |
|---|-----------|-------------|---|
| 1 | 150 ~ 180 | 60 ~ 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245±5 | 5±0.5sec; | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | 2 ~ 10 | /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260±5	10±1 sec.	Temp.:260±5	Time:10±1 sec
-------	-----------	-------------	---------------

