






Parameter	Symbol	Rating	Unit
Peak pulse power ( $t_p = 8/20$ s)	$P_K$	420	W
Peak pulse current ( $t_p = 8/20$ s)	$I_{PP}$	7	A
ESD according to IEC61000-4-2 air discharge	$V_{ESD}$	$\pm 30$	KV
ESD according to IEC61000-4-2 contact discharge		$\pm 30$	
Junction temperature	$T_J$	125	
Storage temperature	$T_{STG}$	-55~+150	

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse maximum working voltage	$V_{RWM}$				w 36	V
Reverse leakage current	$I_R$	$V_{RWM} = w 36V$			100	nA
Reverse breakdown voltage <sup>1)</sup>	$V_{BR}$	$I_T = 1mA$	36			V
Clamping voltage <sup>2)</sup>	$V_C$	$I_{PP} = 1A$ $t_p = 8/20$ s		46	48	V
		$I_{PP} = 7A$ $t_p = 8/20$ s		75	77	V
		$V_{ESD} = 8KV$ <sup>3)</sup>		65		V
Junction capacitance	$C_J$	$V_R = 0V$ $f = 1MHz$		15	20	pF
Clamping voltage <sup>4)</sup>	$V_{CL}$	$I_{PP} = 16A$ $t_p = 100ns$		60		V
Dynamic resistance <sup>4)</sup>	$R_{DYN}$			0.22		

**Notes:**

- 1)  $V_{BR}$  is measured with a pulse test current  $I_T$  at an ambient temperature of 25 .
- 2) Non-repetitive current pulse, according to IEC61000-4-5.
- 3) Contact discharge mode, according to IEC61000-4-2.
- 4) TLP parameter:  $Z_0 = 50$  ,  $t_p = 100ns$ ,  $t_r = 2ns$ , averaging window from 60ns to 80ns.  $R_{DYN}$  is calculated from 4A to 16A.








Peak current

Capacitance vs. Reverse voltage


Clamping voltage vs. Peak pulse current





DFN1006-2L

Unit:mm



Rev.01 202108



### Temperature Profile for IR Reflow Soldering(Pb-Free)


**Note:**

- |   |           |             |   |
|---|-----------|-------------|---|
| 1 | 150 ~ 180 | 60 ~ 90sec; | 1.Preheating:150~180 , Time:60~90sec.   |
| 2 | 245±5     | 5±0.5sec;   | 2.Peak Temp.:245±5 , Duration:5±0.5sec. |
| 3 | 2 ~ 10    | /sec.       | 3. Cooling Speed: 2~10 /sec.            |

260±5	10±1 sec.	Temp.:260±5	Time:10±1 sec
-------	-----------	-------------	---------------

/ REEL

Package Type

Units

Dimension

 (unit mm<sup>3</sup>) / REEL