

5 é / Descriptions

*, 4 2 .> // x % ç i E g + 9 * ' 8 â 'ož

DFN1006-2L Plastic Package 1-Line, Bi-directional , ESD Protection Diode.

α^a / Features

- ◁ Stand-off voltage: ±4.5V Max.
- ◁ Transient protection for each line according to IEC61000-4-2(ESD): ±30kV (contact)
IEC61000-4-4 (EFT): 40A (5/50ns)
IEC61000-4-5(surge): 37A (8/20 s)
- ◁ Ultra-low capacitance: CJ = 65pF typ.
- ◁ Low leakage current:
- ◁ Low clamping voltage: VCL =7.0V typ. @ IPP = 16A (TLP)
- ◁ Solid-state silicon technology
- ◁ HF Product

Đ ÷ / Applications

- ◁ Cellular handsets
- ◁ Tablets
- ◁ Laptops
- ◁ Other portable devices
- ◁ Network communication devices

Ã W] Ô . / Equivalent Circuit

• Ū - æ / Pinning

, M V / Marking

• - ~^a ç ož

See Marking Instructions.

Absolute Maximum Ratings(Ta=25 ;)

@ f Parameter	Symbol	f Rating	% y Unit
Peak Pulse Power(t _p = 8/20 s)	P _{PK}	370	W
Peak Pulse Current(t _p = 8/20 s)	I _{PP}	37	A
ESD according to IEC61000-4-2 air discharge	V _{ESD}	±30	KV
ESD according to IEC61000-4-2 contact discharge		±30	
Junction temperature	T _J	125	
Operating temperature	T _{OP}	-40~85	
Lead temperature	T _L	260	
Storage Temperature	T _{STG}	-55~+150	

Definitions of electrical characteristics

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse maximum working voltage	V_{RWM}				± 4.5	V
Reverse leakage current	I_R	$V_{RWM} = \pm 4.5V$			0.1	μA
Reverse breakdown voltage	V_{BR}	$I_T=15.95204021$				

19.

Ô ? d • Ž ¢ / Electrical Characteristic Curve(Ta=25 ; g unless otherwise noted)

Ô ? d • Ž ¢ / Electrical Characteristic Curve c Ta=25 ; g unless otherwise noted d

Ø □ =) φ / Package Dimensions

