

BRESD5V0X1B2ZP

Rev.C Aug.-2025

DFN1006-2L

ESD

DFN1006-2L Plastic Package 1-Line,Bi-directional , ESD Protection Diode.

1ns


20KV

IEC61000-4-2 4 ESD

Ultra small package, Response Time is Typically < 1 ns, ESD > 20 kV per Human Body Model,IEC61000-4-2 Level 4 ESD Protection,HF Product.




MP3

Suitable for cellular phones audio,MP3 players, Digital cameras, Portable devices, mobile telephone and other users.




Parameter	Symbol	Rating	Unit
p			
Peak Pulse Current($t_p = 8/20\mu s$)	I_{PP}	4	A
ESD according to IEC61000-4-2 air discharge	V_{ESD}	± 20	KV
ESD according to IEC61000-4-2 contact discharge		± 20	

/ Electrical Characteristic Curve(Ta=25)




/ Electrical Characteristic Curve(Ta=25)



/ Package Dimensions


DFN1006-2L

Unit:mm



Rev.01 202108

/ Marking Instructions




5U

Note

5U Product Type Code

() / Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- 1 150 180 60 90sec; 1.Preheating:150~180 , Time:60~90sec.
- 2 245±5 5±0.5sec; 2.Peak Temp.:245±5 , Duration:5±0.5sec.
- 3 2 10 /sec. 3. Cooling Speed: 2~10 /sec.

/ Resistance to Soldering Heat Test Conditions

260±5 10±1 sec. Temp.:260±5 Time:10±1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
DFN1006-2L	10,000	10	100,000	6	600,000	7 x8	180x120x180	390x385x205

/ Notices