


Rev.A Jul.-2016

TO-252

Schottky Diode in a TO-252 Plastic Package.

Low power loss, high efficiency.

For use in low voltage,high frequency inverters, free wheeling, and polarity protection applications.







PIN1 Anode


PIN 2,4 Cathode

PIN 3 Anode

See Marking Instructions.

Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage Working Peak Reverse Voltage DC Blocking Voltage	V_{RRM} V_{RWM} V_{RM}	150	V
RMS Reverse Voltage	$V_{R(RMS)}$	105	V
Average Rectified Forward Current	$I_{F(AV)(per\ leg)}$	10	A
	$I_{F(AV)\ total}$	20	A
Non-Repetitive Peak Forward Surge Current	IRWM		





BR

MBRD20150

CT:

Note:


BR: Company Code

MBRD20150 Product Type.

CT: Internal Structure

****: Lot No. Code, code change with Lot No.

Temperature Profile for IR Reflow Soldering(Pb-Free)



Note:

- | | | | |
|---|--------|-----------|--------------------------------------|
| 1 | 25 150 | 60 90sec; | 1.Preheating:25~150 , Time:60~90sec. |
| 2 | 245±5 | | |

25 245 r