

RB551V-40


Rev.

Parameter	Symbol	Rating	Unit
Maximum recurrent peak reverse voltage	V_{RM}	40	V
Continuous forward current	I_O	500	mA
Peak Forward Surge Current, 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	25	A
Total power dissipation	P_D	200	mW
Thermal Resistance, Junction to Ambient Air	R_{JA}	400	/W
Junction Temperature	T		


/ Electrical Characteristic Curve



RB551V-40
Rev. A Sep.-2019



() / Temperature Profile for IR Reflow Soldering (Pb-Free)



Note:

- | | | | | | |
|---|-----|-----|----|----------|---|
| 1 | 150 | 180 | 60 | 90sec; | 1.Preheating:150~180 , Time:60~90sec. |
| 2 | 245 | 5 | 5 | 0.5sec; | 2.Peak Temp.:245 5 , Duration:5 0.5sec. |
| 3 | | | 2 | 10 /sec. | 3. Cooling Speed: 2~10 /sec. |

/ Resistance to Soldering Heat Test Conditions

260 5 10 1 sec. Temp.:260 5 Time:10 1 sec

/ Packaging SPEC.

/ REEL

Package Type	Units					Dimension (unit mm ³)		
	Units/Reel	Reels/Inner Box	Units/Inner Box	Inner Boxes/Outer Box	Units/Outer Box	Reel	Inner Box	Outer Box
SOD-323	3,000	10	30,000	6	180,000	7 ×8	180×120×180	390×385×205